

Model	Series	LED Count	Power (w/m)	Lumens (lm/m)	Voltage (V)	Temp (K)	CRI	IP Rating
TZ-ST01/827	3528	180	14.4	1250	24	2700	>80	IP20
TZ-ST01/830	3528	180	14.4	1300	24	3000	>80	IP20
TZ-ST01/840	3528	180	14.4	1500	24	4000	>80	IP20
TZ-ST01/850	3528	180	14.4	1600	24	5000	>80	IP20
TZ-ST02/827	3528	120	9.6	850	24	2700	>80	IP20
TZ-ST02/830	3528	120	9.6	900	24	3000	>80	IP20
TZ-ST02/840	3528	120	9.6	980	24	4000	>80	IP20
TZ-ST02/850	3528	120	9.6	1080	24	5000	>80	IP20
TZ-ST03/827	2835	120	28	2830	24	2700	>80	IP20
TZ-ST03/830	2835	120	28	2880	24	3000	>80	IP20
TZ-ST03/840	2835	120	28	2940	24	4000	>80	IP20
TZ-ST03/850	2835	120	28	3000	24	5000	>80	IP20
TZ-ST04/DL	3528	240	19.2	1630	24	2700	>80	IP20
TZ-ST04/WW	3528	240	19.2	1680	24	3000	>80	IP20
TZ-ST04/840	3528	240	19.2	1770	24	4000	>80	IP20
TZ-ST04/850	3528	240	19.2	1920	24	5000	>80	IP20
TZ-ST05/827	3014	120	12	1430	24	2700	>80	IP20
TZ-ST05/830	3014	120	12	1460	24	3000	>80	IP20
TZ-ST05/840	3014	120	12	1510	24	4000	>80	IP20
TZ-ST05/850	3014	120	12	1560	24	5000	>80	IP20
TZ-ST06/827	3014	240	20	2400	24	2700	>80	IP20
TZ-ST06/830	3014	240	20	2450	24	3000	>80	IP20
TZ-ST06/840	3014	240	20	2500	24	4000	>80	IP20
TZ-ST06/850	3014	240	20	2600	24	5000	>80	IP20
TZ-ST505060/827	3528	60	14.4	1000	24	2700	>80	IP20
TZ-ST505060/830	3528	60	14.4	1050	24	3000	>80	IP20
TZ-ST505060/840	3528	60	14.4	1250	24	4000	>80	IP20
TZ-ST505060/850	3528	60	14.4	1350	24	5000	>80	IP20


TZ-RF DIMMER