



MODEL	CCT	Beam Angle	Dimmable	IP	Chip	Tilting
TZ-DL058/WH/WW	3000K	15°/25°/38°	Dimmable	IP20	LUMINUS	△ 20°
TZ-DL058/WH/CW	4000K	15°/25°/38°	Dimmable	IP20	LUMINUS	△ 20°
TZ-DL058/BK/WW	3000K	15°/25°/38°	Dimmable	IP20	LUMINUS	△ 20°
TZ-DL058/BK/CW	4000K	15°/25°/38°	Dimmable	IP20	LUMINUS	△ 20°

LED	DRIVER	TRACK	CCT	R9	SDCM	CRI	LM (LED)
15W	400mA		3000 4000	19	<3	90	1450 1550

Photometric Data:

Beam Angle	H (m)	E _c (lx)	D (m)		H (m)	E _c (lx)	D (m)		H (m)	E _c (lx)	D (m)	
			DH	DV			DH	DV			DH	DV
15°	1.0	6137	0.27	0.27	1.0	3540	0.40	0.40	1.0	1855	0.70	0.70
25°	2.0	1534	0.54	0.54	2.0	885	0.81	0.81	2.0	463	1.39	1.39
38°	2.5	987	0.67	0.67	2.5	566	1.01	1.01	2.5	296	1.74	1.74
	3.0	681	0.80	0.80	3.0	393	1.21	1.21	3.0	206	2.09	2.09
	4.0	483	1.07	1.07	4.0	221	1.62	1.62	4.0	115	2.78	2.78

TZ-DL058-3000K-15W-LUMINUS-150 TZ-DL058-3000K-15W-LUMINUS-300 TZ-DL058-3000K-15W-LUMINUS-300