



MODEL	Beam Angle	Dimmable	IP	Chip	Tilting	Turning
TZ-TR007B	15°/25°/45°	Optional	IP20	LUMINUS	90°	350°

2700K AND 5000K ARE OPTIONAL

AVAILABLE IN BLACK AND WHITE

LED	DRIVER	TRACK	CCT	R9	SDCM	CRI	LM (LED)
20W	500mA	1 Circuit 3 Circuit	3000 4000	19	<3	90	1840 2040

### Photometric Data:

H (m)	E <sub>0</sub> (lx)	D (m)		H (m)	E <sub>0</sub> (lx)	D (m)		H (m)	E <sub>0</sub> (lx)	D (m)	
		ØH	DV			ØH	DV			ØH	DV
1.0	10137	0.30	0.36	1.0	7165	0.38	0.36	1.0	2637	0.64	0.64
2.0	2534	0.61	0.61	2.0	1795	0.76	0.76	2.0	659	1.27	1.27
2.5	1621	0.74	0.74	2.5	1149	0.95	0.95	2.5	421	1.59	1.59
3.0	1124	0.91	0.91	3.0	798	1.14	1.14	3.0	293	1.91	1.91
4.0	633	1.22	1.22	4.0	448	1.52	1.52	4.0	164	2.54	2.54

TZ-TR007B-3000K-20W-LUMINUS-15D      TZ-TR007B-3000K-20W-LUMINUS-25D      TZ-TR007B-3000K-20W-LUMINUS-45D